

JNT - EVC10



Features

- Stylish durable design
- Top quality PC, Anti-UV treatment, Automotive coating
- IK08 & Type3 for indoor & outdoor use
- Switchable from 48A to 16A
- RFID Card reader
- 4.3" LCD screen
- LED indicator
- LAN standard, 4G / Wi-Fi / Emergency stop optional
- OCPP 1.6J
- SAEJ1772 charging plug with 18ft cable



Wall-mounted



Single pedestal



Back-to-back pedestal



Back-to-back pedestal with
cable management system



Dual side-to-side cable
management system

Level 2 AC EV Charger

Model No.	JNT-EVC10/16AC	JNT-EVC10/32AC	JNT-EVC10/40AC	JNT-EVC10/48AC
Input Voltage	208-240Vac			
Frequency	50-60Hz			
Amperage	16A	32A	40A	48A
Max. Power Output	3.8kW	7.6kW	9.6kW	11.5kW
Function				
User Authentication	RFID (ISO 14443)			
Network	LAN Standard (4G or Wi-Fi Optional with Surcharge)			
Connectivity	OCPP 1.6 J			
Protection & Standard				
Certificate	ETL & FCC			
Charging Interface	SAE J1772 Compliant, Type 1 Plug			
Safety Compliance	UL2594, UL2231-1/-2			
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection			
Environmental				
Operating Temperature	-22°F to 122°F			
Indoor / Outdoor	IK08, Type 3 enclosure			
Relative Humidity	Up to 95% non-condensing			
Cable Length	18ft Standard (25ft Optional with Surcharge)			
Dimensions & Weights				
Product Dimensions	13.8" x 9.8" x 5.1"			
Package Dimensions	19.6" x 13.7" x 10.7"			
Net Weight	13.8lbs	13.8lbs	16.8lbs	18.1lbs
Gross Weight	16.1lbs	16.1lbs	19.0lbs	20.3lbs
Pedestal				
	JNT-SP	JNT-BBP	JNT-BBPC	JNT-SSPC
Dimensions	10.6" x 6.1" x 54.9"	10.6" x 6.1" x 54.9"	15.7" x 8.7" x 78.2"	28.0" x 8.7" x 78.2"
Net Weight	28.7lbs	28.7lbs	97lbs	118lbs
Gross Weight	37.5lbs	37.5lbs	113lbs	140lbs
Product Material	Powder Coated Steel			